AGRICULTURE & FORESTRY



PASSION TO PERFORM



HIGH-PERFORMANCE FILTRATION AND CONTAMINATION MONITORING SOLUTIONS FOR THE AGRICULTURAL SECTOR

Designed to thrive in the most challenging working conditions, MP Filtri's comprehensive range of products delivers the best in reliability and quality and has proven itself in the agricultural sector for 60 years.

Enhancing efficiency

Reduced waste

MP Filtri has always forged close partnerships with customers thanks to its commitment to meeting their needs and delivering effective solutions. The company offers a wide range of high-performance products including:



High Pressure Filters



Low Pressure Filters

MDH



Return Filters

Elixir[®] Filters



SFEX Series Suction filters

RFEX Series Return filters

LFEX Series Low Pressure filters

PRODUCTS FHP

MAIN

High Pressure Filters



RELIABILITY AND QUALITY WHY MP FILTRI IS THE PERFECT PARTNER

State-of-the-art research and development programmes ensure our products are extensively tested and perfected in a cutting-edge laboratory. A passion for innovations drives everything we do.

Technology and experience are in the company's DNA

THE MAIN FEATURES THAT DISTINGUISH OUR PRODUCTS ARE:

Full control over every element of production from design to delivery

A wide range of precise customisation options

The latest in Research and Development technology

Innovative design

Outstanding support in the field

🔶 Fast, reliable delivery times



GUARANTEED PERFORMANCE

MULTI-PASS ISO 16889

The ISO Multipass test evaluates the characteristics (or performance) of a filter element, providing data on efficiency and capacity.

ISO standard filtration compared						
β _{x(c)} > 1000 ISO 16889	Filter media code MP Filtri					
5 µm _(c)	A(00)03					
7 μm _(c)	A(00)06					
10 μm _(c)	A(00)10					
16 μm _(c)	A(00)16					
21 µm _(c)	A(00)25					


 $\frac{\begin{array}{c} \text{Upstream} \\ \text{particles number > X } \mu m_{(c)} \\ \hline \\ \hline \\ \text{Downstream} \\ \text{particles number > X } \mu m_{(c)} \end{array} = \beta_{x(c)}$

Designed to thrive in even the most challenging working conditions


Full control over production from design to delivery



STABILITY OF BETA RATING DEGREE OF FILTRATION A(00)10, β10 μm_(c) >1000



HIGH EFFICIENCY IN ALL CONDITIONS



HYDRAULIC FILTRATION

Designing an effective filtration system requires a precise evaluation of its specific features, including: sensitivity of the individual components, degree and type of contamination, circuit pressure,

SUCTION FILTERS

S S flow rate, environmental conditions, fluid used and intervention cycles with a guarantee of a longer life of the machines than expected.

CTDO			up to	Q _{max}		
STRC Submerged suction filter,			l/min	gpm		
with bypass			875	231		
RETURN		D		0		
FILTERS	up to	P _{max}	up to	Q _{max}	MPFX	***
	bar	psi	l/min	gpm		MPTX
MDH "Bubble-free" deaeration filter	8	116	750	198	Tank top semi-immersed filter, easy filter element servicing	
allows the reduction of air inflow into the tank	10	145	500	132		semi-immersed filter
					with air breather, easy filt	er element servicing

ELIXIR [®] guarantees easy maintenance by replacing only the filter element FEX	up to	P _{max}	up to	Q _{max}			j
with a lower environmental impact than previous models	bar	psi	l/min	gpm	SFEX SERIES - Suction RFEX SERIES - Return	ar and	
	16	232	300	79	LFEX SERIES - Low pressure		



RETURN / SUCTION FILTERS

INIROY				
Tank top filter	up to	P _{max}	up to	Qmax
with combined filtration on return and suction	bar	psi	l/min	gpm
to the inlet at the hydrostatic transmissions in closed loop	10	145	300	79

HIGH PRESSURE FILTERS

FMM		up to P _{max}		Qmax	
	bar	psi	l/min	gpm	
ure filter					FHP
and reduced weight	420	6092	300	79	High pressure filter with outlet check valve
	420	6092	710	198	or reverse flow valve options
	act dimensions	ure filter act dimensions	ure filter act dimensions ed weight 420 6092	barpsiJure filter act dimensions ad weight1/min4206092300	barpsiI/mingpmact dimensions ad weight420609230079



LOW PRESSURE FILTERS

LMP	up to	D P _{max}	up to Q _{max}		
Durable In-line filter with a wide range	bar	psi	l/min	gpm	
of element media options, including water removal	60	870	365	96	

FILTER ELEMENTS

DIFFERENT OPTIONS OF FILTER ELEMENTS WITH THE MYCLEAN AND ZEROSPARK® CONCEPTS

Wide range of filter elements in various filtration grades for all MP Filtri filters and as market interchanges.



zerospark+ THE ANTI-STATIC FILTERS THE ZANTISTATIC CONCEPT FOR OUR FILTERS



TANK ACCESSORIES

The complete range of tank accessories for hydraulic circuits comprises breather filters, filler and breather filters, filler caps, visual and electrical level indicators, pressure gauges selectors, flanges for fixing the oil tubes on the tank cover and inspection doors. Filler and breather filters have a dual function at the tank inlet in the filtration of the incoming air and the pre-filtration of the fluid through the basket, in order to prevent the entry of foreign bodies during the filling or refilling operations.

Filler and breather fillers have a dual function at the

AIR BREATHERS AND FILLER PLUGS

TAP90 Filling caps and air breathers with multiple technical solutions TAP114 Nvlon oil filler

and air breather

filler cap

 up to P_{max}

 I/min
 gpm

 550
 145

145

423

VISUAL OIL LEVEL INDICATORS

550

1600

TA80 Metal oil filler and air breather filler cap

LVA

Available in three sizes, to monitor the fluid in the tank





Drive couplings provide the means by which power is transmitted from the electric motor

POWER TRANSMISSION

ic motor



The e-PTO coupling is specifically for electrically powered power take-offs

BELL-HOUSINGS

Bell-Housings are used as connecting elements between IEC electric motors and a wide range of hydraulic pumps available on the international market

CONTAMINATION CONTROL SOLUTIONS

MP Filtri designs and manufactures a complete range of contamination control solutions aimed at increasing the life and the productivity of the hydraulic circuits. The technology developed by our Contamination Monitoring Products division allows preventive and predictive maintenance, guaranteeing

ICM 2.0

In-line

Contamination

Monitor

maximum continuity of operation, a longer life cycle of the components and a relative reduction in costs. A complete solution that combines highly functional and energy-efficient systems with a wide range of after-sales services.

CONTAMINATION MONITORING PRODUCTS

LPA3

Portable Light

Extinction Particle

Analyse



CML4 Compact Portable Contamination Monitor





ICM 4.0





UFM 041



MOBILE FILTRATION

UNITS



UFM 091 UFM 181 UFM 919

Wifi-enabled In-line Contamination Monitor

ed ination 15

15 l/min 34 l/min (3.96 gpm) (8.98 gpm)

UFM 015

up to Q_{max}

50 I/min 9 (13.20 gpm) (23.

UFM 051

90 I/min / 180 I/min (23.77 gpm / 47.55 gpm)



CANADA • CHINA • FRANCE • GERMANY • INDIA • SINGAPORE UNITED ARAB EMIRATES • UNITED KINGDOM • USA

HQ



PASSION TO PERFORM

in 🖾 🖻 f



MF002000001 EN - 2024.09

Filtri reserves the right to make modifications to the models and versions of the described products at any time for both technical and/or co For updated information please visit our website: www.mpfiltri.com. The colors and the pictures of the products are purely indicat Any reproduction, partial or total, of this document is strictly forbidden. All rights are strictly reserved